

Butyl Products Ltd.

11 Radford Crescent, Billericay, Essex CM12 0DW, England.

Tel: +44 (0)1277 653281 **Fax**: +44 (0)1277 657921

E-mail: enquiries@butylproducts.co.uk

www.butylproducts.co.uk Skype: butyl.office



Landflex PVC1100P

Typical Properties	Typical Values
Width	265cm
Colour	Beige 1695
Yarn	100% PES 1100 d/tex 12 x 12 threads / cm
Total weight DIN EN ISO 2286-2	1100g/m²
Tensile strength N/5cm EN ISO 1421-1	Warp 4000 Weft 3500
Tear strength N DIN53 363	Warp 600 Weft 500
Coating adhesion EN ISO 2411	125N / 5cm
Temperature resistance DIN EN 1876-2	-30/ + 70°C
Lightfastness	8
Special properties	Special quality for contact with potable water and food
Application	Flexible containers for drinking water bladder tanks
Waterproofness	>200 Kpa
The information herein is based upon data obtained by the manufacturer and is considered	

The information herein is based upon data obtained by the manufacturer and is considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data. This information is furnished upon the condition that the person receiving it shall evaluate its suitability for the specific application.