

Butyl Products Ltd. 11 Radford Crescent, Billericay, Essex CM12 0DW, England. Tel: +44 (0)1277 653281 Fax: +44 (0)1277 657921 E-mail: enquiries@butylproducts.co.uk www.butylproducts.co.uk



## Landflex PVC1100PG (Potable - Nato Green)

Typical Properties	Typical Values
Base cloth	PES / PES
Total weight (approx.)	1100 g/m²
Base cloth weight (approx.)	275 g/m <sup>2</sup>
Base cloth construction	Panama 2/2
Width	265 cm
Construction	12/13 threads/cm
Coating calender	Dull
Lacquering	Dull lacquer
Breaking strength	4000 N / 5cm
Tear strength	600 N
Adhesion	100 N / 5 cm
Temperature resistance	-30 <sup>°</sup> to +70 <sup>°</sup> C
Lightfastness	8 plus
Colour	Beige 1695 / NATO green RAL 6014
Special properties	Special quality for contact with potable water and food on beige side only.
The information herein is based upon data obtained by the manufacturer and is considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data. This information is furnished upon the condition that the person receiving it shall evaluate its suitability for the specific application.	

TJD/SS 01/2015 Rev.A

